

Koheras AcoustiK™

Multi-channel fiber laser system

- Single frequency operation
- Ultra low phase and vibration noise
- Turn-key 19" 3U benchtop box system
- Available with KHz frequency modulation (option)

Koheras AcoustiK™ is a 8-channel single frequency DFB (distributed feedback) fiber laser system with an extremely low phase and vibration noise, produced for multi-channel sensor interrogation systems.

The system is supplied as a stand-alone unit in a 19" 3U rack system including controller electronics and is delivered with a suitable power supply.



Optical specifications	
Koheras AcoustiK™	E15
Center wavelength [nm] ¹	8 channels within 1530-1565
Laser emission	CW - single frequency
Beam quality	M ² < 1.05
Output power [mW] (per laser)	Up to 50 W
Line width (120 µsec) [kHz]	< 1
Phase-noise [µrad/√Hz] 1m opt. path	<-120@500MHz/ <-110@10Hz
RIN peak [MHz]	app. 0.3
RIN level [dBc/Hz]	<-115@1MHz/<-140@10MHz
Optical S/N [dB] (50 pm res.)	> 50 (depend. on wavelength)
PM output	Optional
Thermal tuning	Standard
Thermal tuning range [nm]	> 0.6
Fast Piezo tuning capability	Optional
Piezo-electric tuning range [pm] ²	> 16 (0-200 V DC)
Piezo-electric tuning bandwidth [kHz] ³	up to 100
Optical monitor output	Incl. (FC/APC)

1. The center wavelength is selectable within the specified range.
2. External piezo driver required.
3. All optical specifications are valid up to 10kHz PZT bandwidth.

Key features

- Stable single mode and single polarisation operation
- Burst noise and mode hop free operation
- Unprecedented low phase and intensity noise
- Ultra narrow linewidth
- Reduced susceptibility to vibration noise
- High wavelength selectability within ITU grid
- Reliable stand-alone unit in a 19" 3U rack system
- Digital control interface

Examples of applications

- Sensor interrogation for oil and gas exploration

Technical specifications	
KOHERAS AcoustiK™	E15
Power supply requirements [VDC]	90-240 VAC; 50-60Hz
Fiber pigtail length [m]	> 1
Connectors	FC/APC or collimated
Dimensions	19" 3U
Operating temperature range [°C]	15 - 40
Storage temperature range [°C]	-20 - 50

Specifications are subject to change without notice.
April 2010 ©Copyright NKT Photonics A/S



Acoustik-100413

NKT Photonics A/S (Headquarters)
Blokken 84 • 3460 Birkerød • Denmark
Phone: +45 4348 3900
Fax: +45 4348 3901
www.nktphotonics.com

NKT Photonics GmbH
Schanzenstrasse 39 • Bldg D9-D13
51063 Cologne • Germany
Phone: +49 221 99511-0
Fax: +49 221 99511-650

NKT Photonics Inc.
1400 Campus Drive West • Morganville
NJ 07751 • USA
Phone: +1 732 972 9937
Fax: +1 732 414 4094